

TACTILITE ST-2015



ANTI-STATIC PROTECTIVE GLOVE WITH ULTRA-LIGHTWEIGHT LINER AND BREATHABLE MICRO FOAM COATING FOR PRECISION HANDLING

Ultra-thin construction enhances hand mobility, while the breathable coating promotes comfort during extended Component-level operations and specifically assembly operations.

Engineered for mechanical works and ESD-sensitive environments, this glove helps dissipate electrostatic charges while maintaining exceptional tactile sensitivity and finger dexterity.

FEATURES

- **ESD-Safe Breathable Liner** reduces heat build-up while providing controlled static dissipation for long tasks
- **FlexHold™** Stability focused construction that limits over flex and preserves fit and grip structure
- **CoreArn™** Reinforced liner framework that resists distortion and material fatigue over extended use
- **Grip Reliability Design** improves steady handling during daily mechanical work tasks
- **TruTouch™** Fingertip optimized zones for precise handling, tactile clarity, and touchscreen interaction
- **AirWeave™** Breathable knit structure that promotes airflow and thermal regulation across the glove
- **Micro-Foam Nitrile Palm** delivers lightweight breathability with 360° tactility and durable grip performance
- **Ergonomic Hand Contour** delivers fatigue-free comfort for all-day wear through advanced hand shaping

STANDARDS

ANSI ABR	ANSI PUN	DEXTERITY
4	2	5
ANSI/ISEA 105 A1 4 2	EN 388:2016 *A1-2018 4131A	ANSI/ISEA 105 CONDUCTIVE HEAT
	EN 407:2020 X1XXXX	EN ISO 21420:2020 *A1-2024 CE CAT II
		EN 16350:2014

MATERIALS

Liner: Anti-Static Nylon, Spandex
Coating: Nitrile Foam
Cuff Style: Elastic Knit Wrist

SIZES

7	S
8	M
9	L
10	XL
11	2XL

PACKING DETAILS

1	Pair Per Polybag Retail Ready
144	Pairs Per Carton




GRYX™ platform adapts to any heavy-duty mechanical glove. Built with flex stabilization, superior liner strength, and mapped dimensional control for unbeatable protection.

ESSENTIAL TECHNOLOGIES



APPLICATIONS





TruTouch™
Fingertip-optimized zones engineered for precision feel and touchscreen interaction



AirWeave™
Breathable knit structure that promotes airflow and heat regulation



DryHold™
Internal liner system that wicks away sweat and moisture



FlexFit™
Anatomical glove shaping that follows the natural curves and motion of the hand




EdgeLock™
Reinforced cuff architecture designed to hold its shape and prevent fraying

Nitrile Foam Palm Coating for Excellent Grip

Anti-Static Knit Liner for Electrostatic Control



CORE-ARN
Structural reinforcement that resists fit collapse



FLEXHOLD
Stabilizes motion zones to reduce over-flex and fabric failure



Color Coded Hem for Quick Size Identification

Elastic Knit Cuff for Secure Fit

ENGINEERED WITH STEGO TECHNOLOGIES

PERFORMANCE & COMPLIANCE ST-2015 meets the requirements of applicable EN & ANSI/ISEA standards.

EN ISO 21420:2020
+A1:2024



EN ISO 21420:2020+A1:2024
General Requirements
Dexterity: 5

EN 407:2020



X1XXXX

EN 407:2020
Protection Against Thermal Risks
Limited Flame Spread: X
Contact Heat: 1
Convective Heat: X
Radiant Heat: X
Small Splashes of Molten Metal: X
Large Quantities of Molten Metal: X

ANSI/ISEA 105



CONDUCTIVE HEAT

ANSI/ISEA 105-2024
ASTM F1060-18
Conductive Heat Resistance
Level 1: 80°C (176°F)
Maximum Contact Temperature

EN 388:2016
+A1:2018



4131A

EN 388:2016+A1:2018
Protection Against Mechanical Risks
Abrasion Resistance: 4
Blade Cut Resistance (Coupe Test): 1
Tear Resistance: 3
Puncture Resistance: 1
Cut Resistance (TDM 100 Test-ISO 13997): A

ANSI/ISEA 105



ANSI/ISEA 105-2024
Mechanical Protection
Cut Resistance: A1
Abrasion Resistance: 4
Puncture Resistance: 2

EN 16350:2014



EN 16350:2014
Electrostatic Properties
Vertical Electrical Resistance
(Tested to EN 1149-2)

PACKAGING INFORMATION

	7 / S	8 / M	9 / L	10 / XL	11 / 2XL
MASTER CARTON DIMENSION	60X44X26 CM	60X44X26 CM	60X44X26 CM	60X44X26 CM	60X44X26 CM
NET WEIGHT	6.60 KG	7.00 KG	7.40 KG	8.20 KG	8.50 KG
GROSS WEIGHT	7.50 KG	8.00 KG	8.40 KG	9.20 KG	9.60 KG
CBM	0.069	0.069	0.069	0.069	0.069
HS CODE	61161000	61161000	61161000	61161000	61161000



Responsibly
Produced



Washable for
Extended Use Life

LIMITATION OF USE

Properly fitting safety gloves are crucial for safety. Poorly-fitting gloves cause irritation and hinder hand movements. Ensure they meet your required safety level and fit comfortably for optimal protection and functionality. The glove should not be worn in areas where there's a risk of entanglement or where there are moving parts. Avoid using gloves if there are signs of damage or defects.