



TACTI-FLEX ST-2025



ANSI 5-ABR ADVANCED ERGONOMIC SEAMLESS KNIT GLOVE WITH DIMPLED FOAM NITRILE SUPER GRIP FOR VERSATILE ASSEMBLY APPLICATIONS

Anti-skid knitted construction flexes naturally around stress areas, promoting unrestricted movement and helping minimize hand fatigue during repetitive tasks.

Dimpled foam nitrile surface disperses fluids on contact, enhancing grip and control while maintaining elevated dexterity across diverse working conditions.

FEATURES

- **Heavy Handling Protection** resists abrasion and tearing from constant contact with tools and materials
- **CoreForm™** Structural reinforcement that stabilizes glove shape and resists collapse under mechanical stress
- **TaskFlex™** Mapped flexibility system aligned to stress zones for controlled movement and reduced bunching
- **Lightweight Breathable Liner** stays comfortable and breathable during extended mechanical work
- **AirWeave™** Breathable knit structure that promotes airflow and thermal regulation across the glove
- **FlexFit™** Anatomical shaping engineered to follow natural hand movement for stable fit and controlled motion
- **Micro-Textured Pattern** enhances grip, durability, and cushioning for precision handling
- **Innovative Coating Cell Structure** disperses fluid through micro-channels for improved handling control

STANDARDS



MATERIALS

Liner: Nylon, Spandex
Coating: Microfoam Nitrile
Cuff Style: Elastic Knit Wrist

SIZES

7	S
8	M
9	L
10	XL
11	2XL


PACKING DETAILS

1	Pair Per Polybag Retail Ready
144	Pairs Per Carton



GRYX™ platform adapts to any heavy-duty mechanical glove. Built with flex stabilization, superior liner strength, and mapped dimensional control for unbeatable protection.

APPLICATIONS





MECHANICAL PROTECTION

HAND PROTECTION ENGINEERED. ACHIEVED.



ST-2025 TACTI-FLEX




AirWeave™
Breathable knit structure that promotes airflow and heat regulation



FlexFit™
Anatomical glove shaping that follows the natural curves & motion of the hand

Microfoam Nitrile with Dimpled Pattern for Grip & Control

Lightweight Nylon Knit for Enhanced Comfort & Breathability



CORE FORM
Reinforced liner structure for dimensional durability



TASK FLEX
Movement-tuned flexibility mapped to stress points



Color Coded Hem for Quick Size Identification

Elastic Knit Cuff for Secure Fit

ENGINEERED WITH STEGO TECHNOLOGIES

PERFORMANCE & COMPLIANCE

ST-2025 meets the requirements of applicable EN & ANSI/ISEA standards.

EN ISO 21420:2020
+A1:2024



EN ISO 21420:2020 +A1:2024
General Requirements
Dexterity:

5

EN 407:2020



X1XXXX

EN 407:2020
Protection Against Thermal Risks
Limited Flame Spread: X
Contact Heat: 1
Convective Heat: X
Radiant Heat: X
Small Splashes of Molten Metal: X
Large Quantities of Molten Metal: X

ANSI/ISEA 105



CONDUCTIVE HEAT

ANSI/ISEA 105-2024
ASTM F1060-18
Conductive Heat Resistance
Level 1: 80°C (176°F)
Maximum Contact Temperature

EN 388:2016
+A1:2018



4131A

EN 388:2016 +A1:2018
Protection Against Mechanical Risks
Abrasion Resistance: 4
Blade Cut Resistance (Coupe Test): 1
Tear Resistance: 3
Puncture Resistance: 1
Cut Resistance (TDM 100 Test-ISO 13997): A

ANSI/ISEA 105



ANSI/ISEA 105-2024
Mechanical Protection
Cut Resistance: A1
Abrasion Resistance: 5
Puncture Resistance: 2

PACKAGING INFORMATION

	7 / S	8 / M	9 / L	10 / XL	11 / 2XL
MASTER CARTON DIMENSION	60X44X26 CM	60X44X26 CM	60X44X26 CM	60X44X26 CM	60X44X26 CM
NET WEIGHT	7.50 KG	7.80 KG	8.00 KG	8.20 KG	8.50 KG
GROSS WEIGHT	8.50 KG	8.70 KG	9.00 KG	9.30 KG	9.50 KG
CBM	0.069	0.069	0.069	0.069	0.069
HS CODE	61161000	61161000	61161000	61161000	61161000



Responsible
Produced



Washable for
Extended Use Life

LIMITATION OF USE

Properly fitting safety gloves are crucial for safety. Poorly-fitting gloves cause irritation and hinder hand movements. Ensure they meet your required safety level and fit comfortably for optimal protection and functionality. The glove should not be worn in areas where there's a risk of entanglement or where there are moving parts. Avoid using gloves if there are signs of damage or defects.