

TACTIMAX ST-2060



ANSI 6-ABR HIGH-PERFORMANCE MECHANICAL GLOVE WITH MICROFOAM NITRILE GRIP AND 360° BREATHABLE CONSTRUCTION

Built for demanding mechanical work, durable construction provides strong abrasion resistance while supporting extended use and reduced hand fatigue.

MicroFoam nitrile delivers reliable grip on lightly oiled surfaces, while enhanced breathability promotes continuous airflow and enhanced wearing comfort.

FEATURES

- **Mechanical Work Protection** withstand abrasion and tearing during continuous use in tough environments
- **FlexHold™** Stability focused construction that limits over flex and preserves fit and grip structure
- **CoreForm™** Structural reinforcement that stabilizes glove shape and resists collapse under mechanical stress
- **Secure Grip Design** supports controlled handling during general mechanical and material handling tasks
- **AirWeave™** Breathable knit structure that promotes airflow and thermal regulation across the glove
- **FlexFit™** Anatomical shaping engineered to follow natural hand movement for stable fit and controlled motion
- **Seamless Anti-Skid Knit** delivers high abrasion resistance with maximum comfort and grip control
- **Ergonomic Hand Contour** delivers fatigue-free comfort for all-day wear through advanced hand shaping

STANDARDS



MATERIALS

Liner: Nylon, Spandex
Coating: Microfoam Nitrile
Cuff Style: Elastic Knit Wrist

SIZES

7	S
8	M
9	L
10	XL
11	2XL

PACKING DETAILS

1	Pair Per Polybag Retail Ready
144	Pairs Per Carton




GRYX™ platform adapts to any heavy-duty mechanical glove. Built with flex stabilization, superior liner strength, and mapped dimensional control for unbeatable protection.

ESSENTIAL TECHNOLOGIES



APPLICATIONS



ST-2060
TACTIMAX


AirWeave™
Breathable knit structure
that promotes airflow and
heat regulation




FlexFit™
Anatomical glove shaping
that follows the natural
curves & motion of the hand

Microfoam Nitrile
Coating for Reliable
Wet & Oily Grip

High-Performance
Nylon Knit for
Superior Comfort



**CORE
FORM**
Reinforced liner structure
for dimensional durability



**FLEX
HOLD**
Stabilizes motion zones
to reduce over-flex and
fabric failure



Color Coded Hem
for Quick Size
Identification

Elastic Knit Cuff
for Secure Fit

ENGINEERED WITH STEGO TECHNOLOGIES

PERFORMANCE & COMPLIANCE ST-2060 meets the requirements of applicable EN & ANSI/ISEA standards.

EN ISO 21420:2020
+A1:2024



EN ISO 21420:2020+A1:2024
General Requirements
Dexterity:

5

EN 407:2020



X1XXXX

EN 407:2020
Protection Against Thermal Risks
Limited Flame Spread: X
Contact Heat: 1
Convective Heat: X
Radiant Heat: X
Small Splashes of Molten Metal: X
Large Quantities of Molten Metal: X

ANSI/ISEA 105



**CONDUCTIVE
HEAT**

ANSI/ISEA 105-2024
ASTM F1060-18
Conductive Heat Resistance
Level 1: 80°C (176°F)
Maximum Contact Temperature

EN 388:2016
+A1:2018



4131A


EN 388:2016+A1:2018
Protection Against Mechanical Risks
Abrasion Resistance: 4
Blade Cut Resistance (Coupe Test): 1
Tear Resistance: 3
Puncture Resistance: 1
Cut Resistance (TDM 100 Test-ISO 13997): A

ANSI/ISEA 105



ANSI/ISEA 105-2024
Mechanical Protection
Cut Resistance: A1
Abrasion Resistance: 6
Puncture Resistance: 2

PACKAGING INFORMATION	7 / S	8 / M	9 / L	10 / XL	11 / 2XL
MASTER CARTON DIMENSION	60X44X26 CM	60X44X26 CM	60X44X26 CM	60X44X26 CM	60X44X26 CM
NET WEIGHT	6.10 KG	6.30 KG	6.50 KG	6.70 KG	6.90 KG
GROSS WEIGHT	7.10 KG	7.30 KG	7.50 KG	7.70 KG	8.00 KG
CBM	0.069	0.069	0.069	0.069	0.069
HS CODE	61161000	61161000	61161000	61161000	61161000



LIMITATION OF USE

Properly fitting safety gloves are crucial for safety. Poorly-fitting gloves cause irritation and hinder hand movements. Ensure they meet your required safety level and fit comfortably for optimal protection and functionality. The glove should not be worn in areas where there's a risk of entanglement or where there are moving parts. Avoid using gloves if there are signs of damage or defects.