



NITRI-FOAM GRIP AIR ST-2065



ANSI 6-ABR & ESD COMPLIANT DOUBLE-DIPPED 3/4 NITRILE COATED GLOVE FOR ENHANCED OIL AND LIQUID RESISTANCE

Double nitrile construction helps shield hands from oils, greases, hydrocarbons, and liquid penetration while maintaining dependable protection during demanding applications.

Sandy nitrile-coated surface provides secure grip on wet and greasy components, while the seamless ergonomic liner enhances flexibility, comfort, and resistance to abrasion and tearing.

FEATURES

- **LiquiBlock™** Surface bonded liquid repellent coating that resists oil & fluid absorption while maintaining grip
- **AirWeave™** Breathable knit structure that promotes airflow and thermal regulation across the glove
- **Dual Coating Protection** keeps hands dry while maintaining tactile control during operations
- **Sandy Nitrile Palm** delivers lightweight breathability with 360° flexibility and reliable grip
- **ESD-Safe 3/4 Nitrile Gloves** deliver durability and abrasion resistance for reliable daily protection
- **CoreForm™** Structural reinforcement that stabilizes glove shape and resists collapse under mechanical stress
- **TaskFlex™** Mapped flexibility system aligned to stress zones for controlled movement and reduced bunching
- **Advanced Nitrile Construction** provides a liquid barrier with sandy palm grip for multi-environment control

STANDARDS



ANSI/ISEA 105



EN 388:2016 +A1:2018



ANSI/ISEA 105



EN 407:2020



EN ISO 21420:2020 +A1:2024



EN 16350:2014



MATERIALS

Liner: Anti-Static Nylon, Spandex
Coating: Smooth & Sandy Nitrile
Cuff Style: Elastic Knit Wrist

SIZES

7	S
8	M
9	L
10	XL
11	2XL

PACKING DETAILS

1	Pair Per Polybag Retail Ready
144	Pairs Per Carton




GRYX™ platform adapts to any heavy-duty mechanical glove. Built with flex stabilization, superior liner strength, and mapped dimensional control for unbeatable protection.

ESSENTIAL TECHNOLOGIES



APPLICATIONS





ESSENTIAL
TECHNOLOGY

ST-2065 NITRI-FOAM GRIP AIR

GRAYK
TECHNOLOGY



TruTouch™
Fingertip-optimized zones engineered for precision feel and touchscreen interaction



AirWeave™
Breathable knit structure that promotes airflow and heat regulation




LiquiBlock™
Fluid-repelling surface coating bonded to the glove's exterior



FlexFit™
Anatomical glove shaping that follows the natural curves & motion of the hand

2nd Layer:
Sandy Nitrile
Palm Coating for
Enhanced Grip

Anti-Static Knit
Liner for Electrostatic
Control



**CORE
FORM**
Reinforced liner structure
for dimensional durability



**TASK
FLEX**
Movement-tuned flexibility
mapped to stress points



1st Layer:
3/4 Smooth Nitrile
Base Coating for
Liquid Resistance

Color Coded Hem
for Quick Size
Identification

Elastic Knit Cuff
for Secure Fit

ENGINEERED WITH STEGO TECHNOLOGIES

PERFORMANCE & COMPLIANCE

ST-2065 meets the requirements of applicable EN & ANSI/ISEA standards.

EN ISO 21420:2020
+A1:2024



EN ISO 21420:2020 + A1:2024
General Requirements
Dexterity:

5

EN 407:2020



X1XXXX

EN 407:2020
Protection Against Thermal Risks
Limited Flame Spread:
Contact Heat:
Convective Heat:
Radiant Heat:
Small Splashes of Molten Metal:
Large Quantities of Molten Metal:

X
1
X
X
X
X
X

ANSI/ISEA 105



**CONDUCTIVE
HEAT**

ANSI/ISEA 105-2024
ASTM F1060-18
Conductive Heat Resistance
Level 1: 80°C (176°F)
Maximum Contact Temperature

EN 388:2016
+A1:2018



4131A

EN 388:2016 + A1:2018
Protection Against Mechanical Risks
Abrasion Resistance:
Blade Cut Resistance (Coupe Test):
Tear Resistance:
Puncture Resistance:
Cut Resistance (TDM 100 Test-ISO 13997):

4
1
3
1
A

ANSI/ISEA 105



ANSI/ISEA 105-2024
Mechanical Protection
Cut Resistance:
Abrasion Resistance:
Puncture Resistance:

A1
6
2


EN 16350:2014



EN 16350:2014
Electrostatic Properties
Vertical Electrical Resistance
(Tested to EN 1149-2)

PACKAGING INFORMATION

	7 / S	8 / M	9 / L	10 / XL	11 / 2XL
MASTER CARTON DIMENSION	60X44X26 CM	60X44X26 CM	60X44X26 CM	60X44X26 CM	60X44X26 CM
NET WEIGHT	9.90 KG	10.40 KG	11.00 KG	11.50 KG	12.10 KG
GROSS WEIGHT	11.10 KG	11.40 KG	11.90 KG	12.40 KG	13.00 KG
CBM	0.069	0.069	0.069	0.069	0.069
HS CODE	61161000	61161000	61161000	61161000	61161000



LIMITATION OF USE

Properly fitting safety gloves are crucial for safety. Poorly-fitting gloves cause irritation and hinder hand movements. Ensure they meet your required safety level and fit comfortably for optimal protection and functionality. The glove should not be worn in areas where there's a risk of entanglement or where there are moving parts. Avoid using gloves if there are signs of damage or defects.