



NITRI-MAX ST-2066



ANSI 6-ABR & ESD COMPLIANT FULL COATED GLOVE WITH SANDY NITRILE FINISH FOR RELIABLE HAND CONTROL & ENHANCED LIQUID PROTECTION

Double-layer NBR construction forms a durable barrier against industrial fluids, helping keep hands protected and dry when handling oily and fluid heavy components.

Sandy nitrile surface enhances grip and control, while the flexible seamless liner supports comfortable movement and reduces fatigue during extended heavy mechanical jobs.

FEATURES

- **CoreForm™** Structural reinforcement that stabilizes glove shape and resists collapse under mechanical stress
- **TaskFlex™** Mapped flexibility system aligned to stress zones for controlled movement and reduced bunching
- **ESD-Safe Gloves** withstand abrasion and tearing during continuous use in tough environments
- **LiquiBlock™** Surface bonded liquid repellent coating that resists oil & fluid absorption while maintaining grip
- **FlexFit™** Anatomical shaping engineered to follow natural hand movement for stable fit and controlled motion
- **Sandy Nitrile Palm** coating improves grip allowing extended use & reduced replacement costs
- **Color Coded Cuff Hem** for fast visual identification of glove size

STANDARDS



MATERIALS

Liner: Anti-Static Nylon, Spandex
Coating: Smooth & Sandy Nitrile
Cuff Style: Elastic Knit Wrist

SIZES

7	S
8	M
9	L
10	XL
11	2XL

PACKING DETAILS


1	Pair Per Polybag Retail Ready
144	Pairs Per Carton



ESSENTIAL TECHNOLOGIES



APPLICATIONS





TruTouch™
Fingertip-optimized zones engineered for precision feel and touchscreen interaction




LiquiBlock™
Fluid-repelling surface coating bonded to the glove's exterior



FlexFit™
Anatomical glove shaping that follows the natural curves & motion of the hand

2nd Layer:
Sandy Nitrile
Palm Coating for
Enhanced Grip

Anti-Static Knit Liner
for Electrostatic Control



CORE FORM
Reinforced liner structure for dimensional durability



TASK FLEX
Movement-tuned flexibility mapped to stress points



1st Layer:
Full Smooth Nitrile
Coating for Liquid
Resistance

Color Coded Hem
for Quick Size
Identification

Elastic Knit Cuff
for Secure Fit

ENGINEERED WITH STEGO TECHNOLOGIES

PERFORMANCE & COMPLIANCE

ST-2066 meets the requirements of applicable EN & ANSI/ISEA standards.

EN ISO 21420:2020
+A1:2024



EN ISO 21420:2020 + A1:2024
General Requirements
Dexterity:

5

EN 407:2020



X1XXXX

EN 407:2020
Protection Against Thermal Risks
Limited Flame Spread:
Contact Heat:
Convective Heat:
Radiant Heat:
Small Splashes of Molten Metal:
Large Quantities of Molten Metal:

X
1
X
X
X
X
X

ANSI/ISEA 105



CONDUCTIVE HEAT

ANSI/ISEA 105-2024
ASTM F1060-18
Conductive Heat Resistance
Level 1: 80°C (176°F)
Maximum Contact Temperature

EN 388:2016
+A1:2018



4131A

EN 388:2016 + A1:2018
Protection Against Mechanical Risks
Abrasion Resistance:
Blade Cut Resistance (Coupe Test):
Tear Resistance:
Puncture Resistance:
Cut Resistance (TDM 100 Test-ISO 13997):

4
1
3
1
A

ANSI/ISEA 105



ANSI/ISEA 105-2024
Mechanical Protection
Cut Resistance:
Abrasion Resistance:
Puncture Resistance:

A1
6
2

EN 16350:2014



EN 16350:2014
Electrostatic Properties
Vertical Electrical Resistance
(Tested to EN 1149-2)

PACKAGING INFORMATION

	7 / S	8 / M	9 / L	10 / XL	11 / 2XL
MASTER CARTON DIMENSION	60X44X26 CM	60X44X26 CM	60X44X26 CM	60X44X26 CM	60X44X26 CM
NET WEIGHT	9.90 KG	10.40 KG	11.00 KG	11.50 KG	12.00 KG
GROSS WEIGHT	11.10 KG	11.50 KG	11.80 KG	12.40 KG	13.00 KG
CBM	0.069	0.069	0.069	0.069	0.069
HS CODE	61161000	61161000	61161000	61161000	61161000



Responsibly
Produced



Washable for
Extended Use Life

LIMITATION OF USE

Properly fitting safety gloves are crucial for safety. Poorly-fitting gloves cause irritation and hinder hand movements. Ensure they meet your required safety level and fit comfortably for optimal protection and functionality. of entanglement or where there are moving parts. Avoid using gloves if there are signs of damage or defects.