



NITRI-MAX THERMO ST-2067



ANSI A4 CUT, 6-ABR HIGH-PERFORMANCE SEAMLESS THERMAL GLOVE WITH SOFT BRUSHED ACRYLIC TERRY LINER AND FULL DOUBLE-DIPPED SANDY NITRILE COATING

Engineered for demanding cold-weather and intense mechanical applications, the dual-layer construction delivers excellent thermal retention, softness and flexibility, while maintaining outstanding hand mobility and dexterity.

The full-hand double-dipped sandy nitrile coating provides enhanced resistance to oil, moisture and abrasion, while its rugged textured surface delivers exceptional grip and dependable control in challenging working conditions.

FEATURES

- **Dual-Layer Thermal Liner** enhances insulation and liquid resistance in cold conditions
- **CoreForm™** Structural reinforcement that stabilizes glove shape and resists collapse under mechanical stress
- **TaskFlex™** Mapped flexibility system aligned to stress zones for controlled movement and reduced bunching
- **High Abrasion & Cut Protection** delivers durable flexibility, long wear life, and dexterity with cut resistance
- **CoreTherm™** Integrated insulation layer retains warmth in cold conditions without restricting mobility
- **LiquiBlock™** Surface bonded liquid repellent coating that resists oil & fluid absorption while maintaining grip
- **TruTouch™** Fingertip optimized zones for precise handling, tactile clarity, and touchscreen interaction
- **Color Coded Cuff Hem** for fast visual identification of glove size

STANDARDS

ANSI CUT	ANSI ABR	ANSI PUN
A4	6	4
ANSI/ISEA 105 A4 6	EN 388:2016 +A1:2018 4X42D	ANSI/ISEA 105 2 CONDUCTIVE HEAT
	EN 407:2020 X2XXXX	EN 511:2006 X2X
	EN ISO 21420:2020 +A1:2024 CE CAT II	

MATERIALS

Outer Liner:	Anti-Static Nylon, Spandex
Inner Liner:	Brushed Acrylic Terry
Coating:	Smooth & Sandy Nitrile
Cuff Style:	Elastic Knit Wrist

SIZES

7	S
8	M
9	L
10	XL
11	2XL

PACKING DETAILS

1	Pair Per Polybag Retail Ready
144	Pairs Per Carton




GRYX™ platform adapts to any heavy-duty mechanical glove. Built with flex stabilization, superior liner strength, and mapped dimensional control for unbeatable protection.

ESSENTIAL TECHNOLOGIES



APPLICATIONS





ESSENTIAL
TECHNOLOGY

ST-2067 NITRI-MAX THERMO

GRAYK
TECHNOLOGY



TruTouch™
Fingertip-optimized zones engineered for precision feel and touchscreen interaction



LiquiBlock™
Fluid-repelling surface coating bonded to the glove's exterior



CoreTherm™
Integrated thermal insulation layer for cold environment protection



FlexFit™
Anatomical glove shaping that follows the natural curves and motion of the hand




EdgeLock™
Reinforced cuff architecture designed to hold its shape and prevent fraying




Brushed Acrylic Terry for Lasting Warmth & Comfort

Lightweight Knit Liner Optimized for Breathability



CORE FORM

Reinforced liner structure for dimensional durability



TASK FLEX

Movement-tuned flexibility mapped to stress points

2nd Layer: Sandy Nitrile Palm Coating for Enhanced Grip

Color Coded Hem for Quick Size Identification

Elastic Knit Cuff for Secure Fit

1st Layer: Full Smooth Nitrile Base Coating for Liquid Resistance

ENGINEERED WITH STEGO TECHNOLOGIES

PERFORMANCE & COMPLIANCE

ST-2067 meets the requirements of applicable EN & ANSI/ISEA standards.

EN ISO 21420:2020
+A1:2024



EN ISO 21420:2020+A1:2024
General Requirements

EN 407:2020



EN 407:2020
Protection Against Thermal Risks
Limited Flame Spread: X
Contact Heat: 2
Convective Heat: X
Radiant Heat: X
Small Splashes of Molten Metal: X
Large Quantities of Molten Metal: X

ANSI/ISEA 105



ANSI/ISEA 105-2024
ASTM F1060-18
Conductive Heat Resistance
Level 2: 140°C (284°F)
Maximum Contact Temperature

EN 388:2016
+A1:2018



EN 388:2016+A1:2018
Protection Against Mechanical Risks
Abrasion Resistance: 4
Blade Cut Resistance (Coupe Test): X
Tear Resistance: 4
Puncture Resistance: 2
Cut Resistance (TDM 100 Test-ISO 13997): 0

ANSI/ISEA 105



ANSI/ISEA 105-2024
Mechanical Protection
Cut Resistance: A4
Abrasion Resistance: 6
Puncture Resistance: 4

EN 511:2006



EN511:2006
Protection Against Cold Risks
Convective Cold: X
Contact Cold: 2
Water Penetration: X

PACKAGING INFORMATION

	7 / S	8 / M	9 / L	10 / XL	11 / 2XL
MASTER CARTON DIMENSION	62X52X26 CM	62X52X26 CM	62X52X26 CM	62X52X26 CM	62X52X26 CM
NET WEIGHT	7.20 KG	7.50 KG	7.80 KG	8.10 KG	8.50 KG
GROSS WEIGHT	7.80 KG	8.20 KG	8.50 KG	8.90 KG	9.20 KG
CBM	0.084	0.084	0.084	0.084	0.084
HS CODE	61161000	61161000	61161000	61161000	61161000

Responsibly
Produced

Washable for
Extended Use Life

LIMITATION OF USE

Properly fitting safety gloves are crucial for safety. Poorly-fitting gloves cause irritation and hinder hand movements. Ensure they meet your required safety level and fit comfortably for optimal protection and functionality. The glove should not be worn in areas where there's a risk of entanglement or where there are moving parts. Avoid using gloves if there are signs of damage or defects.