

TACTI-VIZ THERMO ST-2075



ANSI 6-ABR HIGH-VISIBILITY SEAMLESS KNIT THERMAL GLOVE WITH SOFT BRUSHED ACRYLIC TERRY LINER & 3/4 SANDY NITRILE PROTECTION

Engineered two-layer construction with soft brushed acrylic terry lining keeps hands warm in cold conditions without sacrificing dexterity or flexibility.

Sandy nitrile coating with 3/4 coverage provides enhanced grip, abrasion resistance and liquid protection, while extended coverage strengthens knuckle defense for demanding cold-weather handling.

FEATURES

- **Dual-Layer Brushed Acrylic Liner** maintains warmth and moisture control for comfort and flexibility in cold conditions
- **CoreForm™** Structural reinforcement that stabilizes glove shape and resists collapse under mechanical stress
- **TaskFlex™** Mapped flexibility system aligned to stress zones for controlled movement and reduced bunching
- **3/4 Nitrile Sandy Thermo Glove** delivers abrasion and cut resistance with protection against liquid permeation
- **CoreTherm™** Integrated insulation layer retains warmth in cold conditions without restricting mobility
- **LiquiBlock™** Surface bonded liquid repellent coating that resists oil & fluid absorption while maintaining grip
- **TruTouch™** Fingertip optimized zones for precise handling, tactile clarity and touchscreen interaction
- **High-Visibility Design** improves hand awareness in low-light work environments

STANDARDS

ANSI CUT	ANSI ABR	ANSI PUN
A3	6	3
ANSI/ISEA 105 A3 6 3	EN 388:2016 +A1:2018 4X42B	ANSI/ISEA 105 2 CONDUCTIVE HEAT
	EN 407:2020 X2XXXX	EN 511:2006 X2X
	EN ISO 21420:2020 +A1:2024 CE CAT II	

MATERIALS

Outer Shell:	Polyester, Spandex
Inner Liner:	Brushed Acrylic Terry
Coating:	Smooth & Sandy Nitrile
Cuff Style:	Elastic Knit Wrist

SIZES

7	S
8	M
9	L
10	XL
11	2XL

PACKING DETAILS

1	Pair Per Polybag Retail Ready
144	Pairs Per Carton

GRYX
TECHNOLOGY

**CORE
FORM**


**TASK
FLEX**

GRYX™ platform adapts to any heavy-duty mechanical glove. Built with flex stabilization, superior liner strength, and mapped dimensional control for unbeatable protection.

ESSENTIAL TECHNOLOGIES



APPLICATIONS





ESSENTIAL
TECHNOLOGY

ST-2075 TACTI-VIZ THERMO

GRAYK
TECHNOLOGY



TruTouch™
Fingertip-optimized zones engineered for precision feel and touchscreen interaction



LiquiBlock™
Fluid-repelling surface coating bonded to the glove's exterior



CoreTherm™
Integrated thermal insulation layer for cold environment protection



FlexFit™
Anatomical glove shaping that follows the natural curves and motion of the hand




EdgeLock™
Reinforced cuff architecture designed to hold its shape and prevent fraying



Brushed Acrylic Terry for Lasting Warmth & Comfort

Hi-Vis Seamless Lightweight Knit Shell



CORE FORM

Reinforced liner structure for dimensional durability



TASK FLEX

Movement-tuned flexibility mapped to stress points

1st Layer:
3/4 Smooth Nitrile Base Coating for Liquid Resistance

2nd Layer:
Sandy Nitrile Palm Coating for Enhanced Grip

Color Coded Hem for Quick Size Identification

Elastic Knit Cuff for Secure Fit

ENGINEERED WITH STEGO TECHNOLOGIES

PERFORMANCE & COMPLIANCE

ST-2075 meets the requirements of applicable EN & ANSI/ISEA standards.

EN ISO 21420:2020
+A1:2024



EN ISO 21420:2020+A1:2024
General Requirements

EN 407:2020



EN 407:2020
Protection Against Thermal Risks
Limited Flame Spread: X
Contact Heat: 1
Convective Heat: X
Radiant Heat: X
Small Splashes of Molten Metal: X
Large Quantities of Molten Metal: X

ANSI/ISEA 105



ANSI/ISEA 105-2024
ASTM F1060-18
Conductive Heat Resistance
Level 2: 140°C (284°F)
Maximum Contact Temperature

EN 388:2016
+A1:2018



EN 388:2016+A1:2018
Protection Against Mechanical Risks
Abrasion Resistance: 4
Blade Cut Resistance (Coupe Test): X
Tear Resistance: 4
Puncture Resistance: 2
Cut Resistance (TDM 100 Test-ISO 13997): B

ANSI/ISEA 105



ANSI/ISEA 105-2024
Mechanical Protection
Cut Resistance: A3
Abrasion Resistance: 6
Puncture Resistance: 3


EN 511:2006



EN 511:2006
Protection Against Cold Risks
Convective Cold: X
Contact Cold: 2
Water Penetration: X

PACKAGING INFORMATION

	7 / S	8 / M	9 / L	10 / XL	11 / 2XL
MASTER CARTON DIMENSION	60X44X24 CM	60X44X24 CM	60X44X24 CM	60X44X24 CM	60X44X24 CM
NET WEIGHT	6.70 KG	7.00 KG	7.30 KG	7.60 KG	7.90 KG
GROSS WEIGHT	7.70 KG	8.00 KG	8.30 KG	8.60 KG	9.00 KG
CBM	0.063	0.063	0.063	0.063	0.063
HS CODE	61161000	61161000	61161000	61161000	61161000



LIMITATION OF USE

Properly fitting safety gloves are crucial for safety. Poorly-fitting gloves cause irritation and hinder hand movements. Ensure they meet your required safety level and fit comfortably for optimal protection and functionality. The glove should not be worn in areas where there's a risk of entanglement or where there are moving parts. Avoid using gloves if there are signs of damage or defects.