



FLEXILITE ST-6014



LIGHTWEIGHT FLEXIBLE GLOVE WITH CRINKLE LATEX COATING FOR HIGH RESISTANCE GRIP

Ergonomic construction promotes natural hand movement and precise handling, making it suitable for demanding mechanical and general handling tasks.

Crinkle-textured coating helps channel liquids away from the contact surface, providing reliable slip resistance across wet, dry, and greasy environments.

FEATURES

- **FlexFit™** Anatomical shaping engineered to follow natural hand movement for stable fit and controlled motion
- **EdgeLock™** Reinforced cuff construction that holds shape, resists fraying, and supports long term durability
- **Defined Surface Texture** enhances handling feel without affecting grip performance
- **Quick-Entry Cuff Design** allows fast glove removal and re-entry during repeated use
- **General Handling Protection** delivers reliable resistance to surface wear and material breakdown during tool work
- **CoreForm™** Structural reinforcement that stabilizes glove shape and resists collapse under mechanical stress
- **TaskFlex™** Mapped flexibility system aligned to stress zones for controlled movement and reduced bunching
- **Lightweight Liner Structure** delivers comfort and flexibility without added bulk

STANDARDS



MATERIALS

Liner: Polyester
Coating: Crinkled Latex
Cuff Style: Elastic Knit Wrist

SIZES



PACKING DETAILS




GRYX™ platform adapts to any heavy-duty mechanical glove. Built with flex stabilization, superior liner strength, and mapped dimensional control for unbeatable protection.

ESSENTIAL TECHNOLOGIES



APPLICATIONS






FlexFit™
Anatomical glove shaping that follows the natural curves & motion of the hand



EdgeLock™
Reinforced cuff architecture designed to hold its shape and prevent fraying

Crinkle Latex Palm Coating for Secure Grip

Seamless Knit Liner Enhances Flexibility and Comfort



Reinforced liner structure for dimensional durability



TASK FLEX
Movement-tuned flexibility mapped to stress points



Color Coded Hem for Quick Size Identification

Elastic Knit Cuff for Secure Fit

ENGINEERED WITH STEGO TECHNOLOGIES

PERFORMANCE & COMPLIANCE ST-6014 meets the requirements of applicable EN & ANSI/ISEA standards.

EN ISO 21420:2020
+A1:2024



EN ISO 21420:2020 +A1:2024
General Requirements
Dexterity: 5

ANSI/ISEA 105



ANSI/ISEA 105-2024

Mechanical Protection
Cut Resistance:
Abrasion Resistance:
Puncture Resistance:

A1
3
2

EN 388:2016
+A1:2018



3131X

EN 388:2016 +A1:2018
Protection Against Mechanical Risks

Abrasion Resistance: 3
Blade Cut Resistance (Coupe Test): 1
Tear Resistance: 3
Puncture Resistance: 1
Cut Resistance (TDM 100 Test-ISO 13997): X

PACKAGING INFORMATION

	7 / S	8 / M	9 / L	10 / XL	11 / 2XL
MASTER CARTON DIMENSION	52X44X27 CM	52X44X27 CM	52X44X27 CM	52X44X27 CM	52X44X27 CM
NET WEIGHT	6.50 KG	7.30 KG	8.20 KG	9.10 KG	10.10 KG
GROSS WEIGHT	7.30 KG	8.20 KG	9.20 KG	10.20 KG	11.30 KG
CBM	0.062	0.062	0.062	0.062	0.062
HS CODE	61161000	61161000	61161000	61161000	61161000



Responsibly
Produced



Washable for
Extended Use Life

LIMITATION OF USE

Properly fitting safety gloves are crucial for safety. Poorly-fitting gloves cause irritation and hinder hand movements. Ensure they meet your required safety level and fit comfortably for optimal protection and functionality. The glove should not be worn in areas where there's a risk of entanglement or where there are moving parts. Avoid using gloves if there are signs of damage or defects.