



FORTMAX ST-2095



HIGH-MOBILITY **NANOARN™** LINER WITH **ANSI A6 & CUT F** PROTECTION AND DOUBLE-DIPPED **LIQUIBLOCK™** PALM FOR TACTILE SENSITIVITY.

NANOARN™ advanced liner construction combines high cut resistance with exceptional flexibility and tactile sensitivity, supporting precise finger control and natural hand movement.

Double-dipped LIQUIBLOCK™ palm helps resist liquid penetration, while sandy nitrile enhances grip and abrasion resistance; reinforced thumb crotch adds durability. Its lightweight design supports comfortable extended wear.

FEATURES

- **Cut-Resistant Protection** helps guard against lacerations while supporting safe, consistent performance
- **CoreDeflect™** Directional fiber alignment that disperses blade force to reduce slicing penetration
- **TensionForm™** Tension control architecture that regulates stretch and recovery for consistent fit
- **NanoArn™** Lightweight reinforcement layer enhancing strength and structural consistency maintaining dexterity
- **TruTouch™** Fingertip optimized zones for precise handling, tactile clarity, and touchscreen interaction
- **DryHold™** Moisture wicking system that maintains internal dryness and reduces slippage during use
- **Lightweight Liner** delivers excellent handfeel and comfort in the toughest environments
- **Ergonomic Hand Contour** enhances comfort and reduces fatigue for all-day wear

STANDARDS



MATERIALS

Liner: NanoArn™ High Mobility Carbon Blend Cut Liner
Coating: Sandy Nitrile
Cuff Style: Elastic Knit Wrist

SIZES

7	S
8	M
9	L
10	XL
11	2XL

PACKING DETAILS

1	Pair Per Polybag Retail Ready
144	Pairs Per Carton

TEGX™ Gloves are constructed through coordinated elements, delivering controlled strength, engineered accuracy, and stable performance in sharp-risk environments.

ESSENTIAL TECHNOLOGIES



APPLICATIONS





CUT PROTECTION



HAND PROTECTION ENGINEERED. ACHIEVED.



ST-2095 FORTMAX



TruTouch™
Fingertip-optimized zones engineered for precision feel and touchscreen interaction



DryHold™
Internal liner system that wicks away sweat and moisture



LiquiBlock™
Fluid-repelling surface coating bonded to the glove's exterior



FlexFit™
Anatomical glove shaping that follows the natural curves & motion of the hand

High-wear Thumb Reinforcement
Extend Glove Life

High Mobility Carbon Blend Liner for Cut & Zero-Irritation Comfort



Sandy Nitrile Palm Coating for Flexible Grip & Comfort

Color Coded Hem for Quick Size Identification

Elastic Knit Cuff for Secure Fit



Core Reflect

Fiber alignment that disperses blade force away from key contact zones



Tension Form

Engineered knit tension control for natural hand alignment



Nano Arn

Advanced fiber enhancement system designed for lightweight strength and material reinforcement

ENGINEERED WITH STEGO TECHNOLOGIES

PERFORMANCE & COMPLIANCE

ST-2095 meets the requirements of applicable EN & ANSI/ISEA standards.

EN ISO 21420:2020
+A1:2024



EN ISO 21420:2020 + A1:2024
General Requirements
Dexterity: 5

EN 407:2020



X1XXXX

EN 407:2020
Protection Against Thermal Risks
Limited Flame Spread: X
Contact Heat: 1
Convective Heat: X
Radiant Heat: X
Small Splashes of Molten Metal: X
Large Quantities of Molten Metal: X

ANSI/ISEA 105



CONDUCTIVE HEAT

ANSI/ISEA 105-2024
ASTM F1060-18
Conductive Heat Resistance
Level 1: 80°C (176°F)
Maximum Contact Temperature

EN 388:2016
+A1:2018



4X42F

EN 388:2016 + A1:2018
Protection Against Mechanical Risks
Abrasion Resistance: 4
Blade Cut Resistance (Coupe Test): X
Tear Resistance: 4
Puncture Resistance: 2
Cut Resistance (TDM 100 Test-ISO 13997): F

ANSI/ISEA 105



ANSI/ISEA 105-2024
Mechanical Protection
Cut Resistance: A6
Abrasion Resistance: 5
Puncture Resistance: 3

PACKAGING INFORMATION	7 / S	8 / M	9 / L	10 / XL	11 / 2XL
MASTER CARTON DIMENSION	60X46X28 CM	60X46X28 CM	60X46X28 CM	60X46X28 CM	60X46X28 CM
NET WEIGHT	8.00 KG	8.50 KG	9.00 KG	9.50 KG	10.20 KG
GROSS WEIGHT	8.80 KG	9.40 KG	10.00 KG	10.60 KG	11.20 KG
CBM	0.077	0.077	0.077	0.077	0.077
HS CODE	61161000	61161000	61161000	61161000	61161000



Responsible
Produced



Washable for
Extended Use Life

LIMITATION OF USE

Properly fitting safety gloves are crucial for safety. Poorly-fitting gloves cause irritation and hinder hand movements. Ensure they meet your required safety level and fit comfortably for optimal protection and functionality. The glove should not be worn in areas where there's a risk of entanglement or where there are moving parts. Avoid using gloves if there are signs of damage or defects.