





SHELL SERIES ST-8056



ESSENTIAL TECHNOLOGIES



APPLICATIONS



SHELL™ GRD MULTI-HAZARD IMPACT GLOVES WITH **TEGX™ TEXARN™ A5 CUT LINER**, & **TORQUEGUARD™** ANTI-VIBRATION PALM DAMPENING TECHNOLOGY.

Designed for demanding power tool, demolition, and construction applications, these gloves combine A5 cut, back-of-hand impact, vibration, & abrasion protection in one versatile multi-hazard design.

TEGX™ TEXARN™ liner delivers high cut resistance, while SHELL™ GRD hi-vis TPR absorbs impact energy. TORQUEGUARD™ palm technology dampens vibration, shock, and torque for confident control, comfort, and reduced hand fatigue.

FEATURES

- **Shell™ GRD Technology** with high-cut liner delivers tri-hazard protection against impact, vibration, cut, and abrasion hazards
- **ShockShell™** Compressive TPR zones that absorb vertical impact energy
- **TorqueGuard™** Palm-based vibration dampening system reducing transmitted shock and torque
- **Heavy-Duty Rubber Palm Pads** provide maximum shock and vibration protection for lasting comfort during long shifts
- **AirWeave™** Breathable knit structure that promotes airflow and thermal regulation across the glove
- **EdgeLock™** Reinforced construction that holds shape, resists fraying and supports long term durability
- **FlexFit™** Anatomical shaping engineered to follow natural hand movement for stable fit & controlled motion
- **Fusion-Built Ergonomic Fit** enhances breathability, regulates moisture, and reduces hand fatigue

STANDARDS



MATERIALS

Liner: TexArn™ HPPE Blend Liner
Coating: Chloroprene Rubber
Cuff Style: Elastic Knit Wrist

SIZES

7	S
8	M
9	L
10	XL
11	2XL

PACKING DETAILS

1	Pair Per Polybag Retail Ready
60	Pairs Per Carton



ST-8056 SHELL SERIES



AirWeave™
Breathable knit structure that promotes airflow and heat regulation



FlexFit™
Anatomical glove shaping that follows the natural curves & motion of the hand



EdgeLock™
Reinforced cuff architecture designed to hold its shape and prevent fraying

Performance Rubber Palm Pads Reduce Tool Vibration & Absorb Impact Shock


Seamless HPPE Blend Liner for Strength & Flexibility

Molded TPR Impact Protection for Knuckles, Thumb & Full-Length Fingers



Color Coded Hem for Quick Size Identification


Elastic Knit Cuff for Secure Fit



SHOCK SHELL
Vertical impact absorption zones made from compressive TPR



IMPACT FLOW
Sculpted TPR geometry that redirects oblique/angled force



FLEX SPINE
Articulated finger-aligned TPR that allows natural bending



TORQUE GUARD
Glove stabilization panel that locks fit during twisting or torque

ENGINEERED WITH STEGO TECHNOLOGIES

PERFORMANCE & COMPLIANCE

ST-8056 meets the requirements of applicable EN & ANSI/ISEA standards.

EN ISO 21420:2020
+A1:2024



EN ISO 21420:2020 + A1:2024
General Requirements

EN 407:2020



X1XXXX

EN 407:2020
Protection Against Thermal Risks
Limited Flame Spread: X
Contact Heat: 1
Convective Heat: X
Radiant Heat: X
Small Splashes of Molten Metal: X
Large Quantities of Molten Metal: X

ANSI/ISEA 105



CONDUCTIVE HEAT

ANSI/ISEA 105-2024
ASTM F1060-18
Conductive Heat Resistance
Level 2: 140°C (284°F)
Maximum Contact Temperature

EN 388:2016
+A1:2018



4543EP

EN 388:2016 + A1:2018
Protection Against Mechanical Risks
Abrasion Resistance: 4
Blade Cut Resistance (Coupe Test): 5
Tear Resistance: 4
Puncture Resistance: 3
Cut Resistance (TDM 100 Test-ISO 13997): E
Impact Protection: P

ANSI/ISEA 105



ANSI/ISEA 105-2024
Mechanical Protection
Cut Resistance: A5
Abrasion Resistance: 4
Puncture Resistance: 3

EN ISO 10819:2013



TR₁ = 0.86
TR₂ = 0.59

EN ISO 10819:2013
Protective Against Mechanical Vibration & Shock
Medium-Frequency (25-200 Hz): TRM ≤ 0.9
High-Frequency (200-1250 Hz): TRM ≤ 0.6

ANSI/ISEA 138



ANSI/ISEA 138-2019
Level 2 ≤ 6.5kN



LIMITATION OF USE

Properly fitting safety gloves are crucial for safety. Poorly-fitting gloves cause irritation and hinder hand movements. Ensure they meet your required safety level and fit comfortably for optimal protection and functionality. The glove should not be worn in areas where there's a risk of entanglement or where there are moving parts. Avoid using gloves if there are signs of damage or defects.

PACKAGING INFORMATION

	7 / S	8 / M	9 / L	10 / XL	11 / 2XL
MASTER CARTON DIMENSION	60X34X40 CM	60X34X40 CM	60X34X40 CM	60X34X40 CM	60X34X40 CM
NET WEIGHT	15.80 KG	15.60 KG	17.50 KG	18.30 KG	19.30 KG
GROSS WEIGHT	16.70 KG	17.70 KG	18.50 KG	19.40 KG	20.40 KG
CBM	0.082	0.082	0.082	0.082	0.082
HS CODE	61161000	61161000	61161000	61161000	61161000