



CUT PROTECTION



HAND PROTECTION ENGINEERED. ACHIEVED.

SUPER CUT MAX ST-2098



EXCEPTIONAL CUT PROTECTION **TEGX® TEXARN™** BLENDED PARA-ARAMID LINER, **ANSI A7 & CUT F**, WITH SANDY NITRILE PALM

For extreme laceration hazards, the para-aramid liner provides inherent cut resistance and withstands high temperatures without melting or dripping, supporting dependable protection.

Its blended engineered construction provides breathability, tactile sensitivity, secure fit and stability, while sandy nitrile palm delivers superior oil, grease and wet grip with touchscreen compatibility.

FEATURES

- **Extreme Cut Protection** withstands sharp-edge hazards in high-risk industrial environments
- **TexArn™ Max Para-Aramid Liner** provides inherent cut resistance while resisting heat, ignition, and electrical conductivity
- **CutCage™** Reinforcement framework protecting critical contact zones against cutting forces
- **RetentionCore™** Internal stabilization system anchors liner and coating to maintain fit accuracy during prolonged usage
- **TruTouch™** Fingertip optimized zones for precise handling, tactile clarity, and touchscreen interaction
- **DryHold™** Moisture wicking system that maintains internal dryness and reduces slippage during use
- **Sandy Nitrile Coating** delivers breathable comfort with lightweight 360° tactility and reliable grip
- **Extended Cuff Design** provides added wrist coverage for enhanced protection

STANDARDS




MATERIALS

Liner: TexArn™ Max Para-Aramid Blend Cut Liner
Coating: Sandy Nitrile
Cuff Style: Elastic Knit Wrist

SIZES



PACKING DETAILS



TEGX™ Gloves are constructed through coordinated elements, delivering controlled strength, engineered accuracy, and stable performance in sharp-risk environments.

ESSENTIAL TECHNOLOGIES



APPLICATIONS





TruTouch™
Fingertip-optimized zones engineered for precision feel and touchscreen interaction



DryHold™
Internal liner system that wicks away sweat and moisture

Crinkle Latex Palm Coating for Consistent Grip in Dry, Wet & Oily Conditions

Inherently Cut-Resistant TexArn™ Max Para-Aramid Liner Resists Heat & Conductivity




TexArn

Blended yarn system fused for core strength and structural consistency



Cut Cage

Reinforced cut zones placed in high-risk areas



Retention Core

Internal structure that prevents collapse or distortion under stress



Color Coded Hem for Quick Size Identification

Elastic Knit Cuff for Secure Fit

ENGINEERED WITH STEGO TECHNOLOGIES

PERFORMANCE & COMPLIANCE

ST-2098 meets the requirements of applicable EN & ANSI/ISEA standards.

EN ISO 21420:2020
+A1:2024



EN ISO 21420:2020+A1:2024
General Requirements
Dexterity:

5

EN 407:2020



X2XXXX

EN 407:2020

Protection Against Thermal Risks

Limited Flame Spread:

X

Contact Heat:

2

Convective Heat:

X

Radiant Heat:

X

Small Splashes of Molten Metal:

X

Large Quantities of Molten Metal:

X

ANSI/ISEA 105



CONDUCTIVE HEAT

ANSI/ISEA 105-2024

ASTM F1060-18

Conductive Heat Resistance

Level 2: 140°C (284°F)

Maximum Contact Temperature

EN 388:2016
+A1:2018



4X44F

EN 388:2016+A1:2018

Protection Against Mechanical Risks

Abrasion Resistance:

4

Blade Cut Resistance (Coupe Test):

X

Tear Resistance:

4

Puncture Resistance:

4

Cut Resistance (TDM 100 Test-ISO 13997):

F

ANSI/ISEA 105



ANSI/ISEA 105-2024

Mechanical Protection

Cut Resistance:

A7

Abrasion Resistance:

5

Puncture Resistance:

4

PACKAGING INFORMATION	7 / S	8 / M	9 / L	10 / XL	11 / 2XL
MASTER CARTON DIMENSION	54X35X45 CM	54X35X45 CM	54X35X45 CM	54X35X45 CM	54X35X45 CM
NET WEIGHT	13.80 KG	15.20 KG	16.70 KG	18.20 KG	19.80 KG
GROSS WEIGHT	14.70 KG	16.10 KG	17.70 KG	19.30 KG	21.00 KG
CBM	0.085	0.085	0.085	0.085	0.085
HS CODE	61161000	61161000	61161000	61161000	61161000



Responsible
Produced



Washable for
Extended Use Life

LIMITATION OF USE

Properly fitting safety gloves are crucial for safety. Poorly-fitting gloves cause irritation and hinder hand movements. Ensure they meet your required safety level and fit comfortably for optimal protection and functionality. The glove should not be worn in areas where there's a risk of entanglement or where there are moving parts. Avoid using gloves if there are signs of damage or defects.