



CUT PROTECTION



HAND PROTECTION ENGINEERED. ACHIEVED.

# SUPER CUT ST-6050



## ADVANCED **A7** & **CUT F** PROTECTION WITH **TEGX® TEXARN™** PARA-ARAMID LINER & CRINKLE LATEX COATING FOR SUPERIOR GRIP

TEGX® para-aramid construction is inherently cut resistant and will not melt or ignite, delivering dependable protection against severe cuts across multi-industrial applications.

Crinkle latex delivers exceptional grip and abrasion resistance for heavy-duty work, while the para-aramid liner supports outstanding durability, extended working life, ANSI 5 puncture resistance and EN 407 Contact Heat Level 2 protection.

### FEATURES

- **TEGX® Para-Aramid Liner** provides reliable laceration protection for safe and consistent task performance
- **TexArn™** Blended high-strength yarn core forming the structural foundation of cut resistance
- **RetentionCore™** Internal stabilization system anchors liner and coating to maintain fit accuracy during prolonged usage
- **Crinkle Latex Palm** enhances traction and control in dry, wet, and oily conditions
- **Reliable Grip Control** maintains confident handling of tools, materials, and components throughout the job
- **DryHold™** Moisture-wicking system that maintains internal dryness and reduces slippage during use
- **Ergonomic Hand Contour** enhances comfort and reduces fatigue for all-day wear
- **Elasticated Knit Cuff** helps seal out dirt and debris to keep hands clean and protected

### STANDARDS



### MATERIALS

Liner: TexArn™ Para-Aramid Blend Cut Liner  
Coating: Crinkle Latex  
Cuff Style: Elastic Knit Wrist

### SIZES

|    |     |
|----|-----|
| 7  | S   |
| 8  | M   |
| 9  | L   |
| 10 | XL  |
| 11 | 2XL |

### PACKING DETAILS

|     |                                  |
|-----|----------------------------------|
| 1   | Pair Per Polybag<br>Retail Ready |
| 144 | Pairs Per Carton                 |

**TEGX™** Gloves are constructed through coordinated elements, delivering controlled strength, engineered accuracy, and stable performance in sharp-risk environments.

### APPLICATIONS



### ESSENTIAL TECHNOLOGIES





CUT PROTECTION



HAND PROTECTION ENGINEERED. ACHIEVED.



## ST-6050 SUPER CUT



**Dry Hold™**  
Internal liner system  
that wicks away sweat  
and moisture

Crinkle Latex Palm  
Coating for Consistent  
Grip in Dry, Wet & Oily  
Conditions


TEGX® Para-Aramid  
Blend Liner for Extreme  
Cut Protection



Blended yarn system fused  
for core strength and  
structural consistency



Reinforced cut zones  
placed in high-risk areas



Internal structure that  
prevents collapse or  
distortion under stress



Color Coded Hem  
for Quick Size  
Identification

Elastic Knit Cuff  
for Secure Fit

ENGINEERED WITH STEGO TECHNOLOGIES

### PERFORMANCE & COMPLIANCE

ST-6050 meets the requirements of applicable EN & ANSI/ISEA standards.

EN ISO 21420:2020  
+A1:2024



**EN ISO 21420:2020+A1:2024**  
General Requirements  
Dexterity:

5

EN 407:2020



X2XXXX

**EN 407:2020**  
Protection Against Thermal Risks  
Limited Flame Spread: X  
Contact Heat: 2  
Convective Heat: X  
Radiant Heat: X  
Small Splashes of Molten Metal: X  
Large Quantities of Molten Metal: X

ANSI/ISEA 105



CONDUCTIVE  
HEAT

**ANSI/ISEA 105-2024**  
ASTM F1060-18  
Conductive Heat Resistance  
Level 2: 140°C (284°F)  
Maximum Contact Temperature

EN 388:2016  
+A1:2018



3X44F

**EN 388:2016+A1:2018**  
Protection Against Mechanical Risks  
Abrasion Resistance: 3  
Blade Cut Resistance (Coupe Test): X  
Tear Resistance: 4  
Puncture Resistance: 4  
Cut Resistance (TDM 100 Test-ISO 13997): F

ANSI/ISEA 105



**ANSI/ISEA 105-2024**  
Mechanical Protection

Cut Resistance: A7  
Abrasion Resistance: 5  
Puncture Resistance: 5

| PACKAGING INFORMATION   | 7 / S       | 8 / M       | 9 / L       | 10 / XL     | 11 / 2XL    |
|-------------------------|-------------|-------------|-------------|-------------|-------------|
| MASTER CARTON DIMENSION | 54X35X45 CM | 54X35X45 CM | 54X35X45 CM | 54X35X45 CM | 54X35X45 CM |
| NET WEIGHT              | 13.80 KG    | 15.20 KG    | 16.70 KG    | 18.20 KG    | 19.80 KG    |
| GROSS WEIGHT            | 14.60 KG    | 16.10 KG    | 17.70 KG    | 19.30 KG    | 21.00 KG    |
| CBM                     | 0.085       | 0.085       | 0.085       | 0.085       | 0.085       |
| HS CODE                 | 61161000    | 61161000    | 61161000    | 61161000    | 61161000    |



Responsible  
Produced



Washable for  
Extended Use Life

### LIMITATION OF USE

Properly fitting safety gloves are crucial for safety. Poorly-fitting gloves cause irritation and hinder hand movements. Ensure they meet your required safety level and fit comfortably for optimal protection and functionality. The glove should not be worn in areas where there's a risk of entanglement or where there are moving parts. Avoid using gloves if there are signs of damage or defects.