

N'FLOCK ST-2018



SPECIALIZED NITRILE FLOCK LINED CHEMICAL RESISTANT GLOVES WITH DIAMOND GRIP EN ISO 374-1 TYPE-A

Provides flexibility, tactile sensitivity, and dexterity often lacking in heavier-gauge nitrile, while offering protection against chemical and physical hazards not always found in thinner disposable nitrile.

FEATURES

- **Integrated Flock Lining** keeps hands dry and allows quick donning during repeated on-off use
- **FlexFit™** Anatomical shaping engineered to follow natural hand movement for stable fit and controlled motion
- **Food Contact Approved Gloves** supports hygiene control and safe handling performance
- **Outstanding Tactile Sensitivity** delivers flexibility, dexterity, durability, and all-day comfort
- **Enhanced Chemical Barrier** maintains protective performance during repeated chemical contact for safer extended wear during exposure cycles
- **CoreResist™** Material stabilization technology preventing degradation during repeated chemical contact
- **SealTrace™** Seam integrity system blocks micro-pathways to prevent chemical ingress at transition zones when used for continuous liquid exposure tasks
- **Raised Diamond Palm Pattern** helps maintain control in wet, dry, and oily chemical environments

STANDARDS



MATERIALS

Liner: Cotton Flock
Coating: Diamond Grip Nitrile
Cuff Style: Straight Cuff
Length: 13"

SIZES



PACKING DETAILS




ChemBlock™ delivers consistent multi layer protection across gloves designed for chemical, liquid, and solvent exposure, with a reliable internal resistance structure across every application.

ESSENTIAL TECHNOLOGIES



APPLICATIONS



ST-2018 N'FLOCK



FlexFit™
Anatomical glove shaping that follows the natural curves & motion of the hand

2nd Layer:
Raised Diamond Palm Texture Enhances Grip and Control During Chemical Handling

1st Layer:
Advanced Nitrile Formulation Enhances Chemical Resistance, Flexibility, and Durability



Core Resist
Fatigue-resistant internal matrix that maintains structure under long exposure



Seal Trace
Surface-layer uniformity system that eliminates micro-pathways for fluid entry

Soft Cotton Flock Lining Enhances Comfort and Moisture Absorption During Extended Wear

Straight Cuff Provides Extended Coverage and Added Protection Against Liquid Run-Off

ENGINEERED WITH STEGO TECHNOLOGIES

PERFORMANCE & COMPLIANCE ST-2018 meets the requirements of applicable EN & ANSI/ISEA standards.

EN ISO 21420:2020
+A1:2024



EN ISO 21420:2020+A1:2024
General Requirements
Dexterity: 5

EN ISO 374-1:2016
+A1:2018



EN ISO 374-1:2016+A1:2018
Protection Against Dangerous Chemicals
J - n-Heptane
K - Sodium Hydroxide (40%)
L - Sulphuric Acid (96%)
N - Acetic Acid (99%)
O - Ammonia (25%)
T - Formaldehyde (37%)

EN 374-5:2016



EN ISO 374-5:2016
Protection Against Micro-Organisms

EN 388:2016
+A1:2018




EN 388:2016+A1:2018
Protection Against Mechanical Risks
Abrasion Resistance: 4
Blade Cut Resistance (Coupe Test): 1
Tear Resistance: 0
Puncture Resistance: 1
Cut Resistance (TDM 100 Test-ISO 13997): X



ASTM D 3389-10 / ASTM D 3884-09
Protection Against Abrasion Risks
Abrasion Level: 4
Endurance Threshold: >3,000 Revolutions



Suitable for Contact with Foodstuff



LIMITATION OF USE

Properly fitting safety gloves are crucial for safety. Poorly-fitting gloves cause irritation and hinder hand movements. Ensure they meet your required safety level and fit comfortably for optimal protection and functionality. The glove should not be worn in areas where there's a risk of entanglement or where there are moving parts. Avoid using gloves if there are signs of damage or defects.

PACKAGING INFORMATION	7 / S	8 / M	9 / L	10 / XL	11 / 2XL
MASTER CARTON DIMENSION	41X35X24 CM	41X35X24 CM	41X35X24 CM	41X35X24 CM	41X35X24 CM
NET WEIGHT	8.00 KG	8.30 KG	8.70 KG	9.00 KG	9.40 KG
GROSS WEIGHT	8.90 KG	9.30 KG	9.70 KG	10.00 KG	10.50 KG
CBM	0.035	0.035	0.035	0.035	0.035
HS CODE	40151910	40151910	40151910	40151910	40151910