



CHEM SHIELD ST-8089



NEOPRENE-LATEX FLOCK LINED CHEMICAL GLOVES WITH RAISED DIAMOND GRIP EN ISO 374-1 TYPE-A

Moisture absorbing liner keeps your hands dry. Double-dipped neoprene gloves provide superior protection & versatile resistance from a wide range of chemicals, acids, caustics, solvents, & oils.

FEATURES

- **Protective Integrity Design** maintains protection during splashes, contact, and routine chemical handling
- **CoreResist™** Material stabilization technology preventing degradation during repeated chemical contact
- **SolvLock™** Solvent resistant polymer structure that maintains barrier stability under aggressive exposure
- **Raised Diamond Pattern Palm** supports consistent grip and handling accuracy during repetitive chemical operations
- **DryHold™** Moisture-wicking system that maintains internal dryness and reduces slippage during use
- **FlexFit™** Anatomical shaping engineered to follow natural hand movement for stable fit and controlled motion
- **Flock-Lined Quick-Entry Cuff** enables fast donning and doffing during repeated use
- **Ergonomic Flex Design** moves with the hand to enhance range of motion during precision tasks

STANDARDS



MATERIALS

Liner: Cotton Flock
Coating: Neoprene, Latex
Cuff Style: Straight Cuff
Length: 12.5"

SIZES



7	S
8	M
9	L
10	XL
11	2XL

PACKING DETAILS

1	Pair Per Polybag Retail Ready
120	Pairs Per Carton




ChemBlock™ delivers consistent multi layer protection across gloves designed for chemical, liquid, and solvent exposure, with a reliable internal resistance structure across every application.

ESSENTIAL TECHNOLOGIES



APPLICATIONS



ESSENTIAL TECHNOLOGY

ST-8089 CHEM SHIELD

CHEM BLOCK Technology



DryHold™
Internal liner system that wicks away sweat and moisture



FlexFit™
Anatomical glove shaping that follows the natural curves & motion of the hand

2nd Layer:
Diamond-Pattern Neoprene Palm Enhances Resistance to Acids, Caustics, Solvents and Oils

1st Layer:
Flexible Latex Coating Delivers Comfort, Dexterity & Protective Performance




Soft Cotton Flock Lining Enhances Comfort and Moisture Absorption During Extended Wear

Straight Cuff Provides Extended Coverage and Added Protection Against Liquid Run-Off



Core Resist

Fatigue-resistant internal matrix that maintains structure under long exposure



Solv Lock

Internal structure that prevents collapse or distortion under stress

ENGINEERED WITH STEGO TECHNOLOGIES

PERFORMANCE & COMPLIANCE

ST-2020 meets the requirements of applicable EN & ANSI/ISEA standards.

EN ISO 21420:2020
+A1:2024



EN ISO 21420:2020 + A1:2024
General Requirements
Dexterity: 5

EN ISO 374-1:2016
+A1:2018



EN ISO 374-1:2016 + A1:2018
Protection Against Dangerous Chemicals
A - Methanol
K - Sodium Hydroxide (40%)
L - Sulphuric Acid (98%)
N - Acetic Acid (99%)
P - Hydrogen Peroxide (30%)
T - Formaldehyde (37%)

EN 374-5:2016



EN ISO 374-5:2016
Protection Against Micro-Organisms

EN 388:2016
+A1:2018




3111X

EN 388:2016 + A1:2018
Protection Against Mechanical Risks
Abrasion Resistance: 4
Blade Cut Resistance (Coupe Test): 1
Tear Resistance: 2
Puncture Resistance: 1
Cut Resistance (TDM 100 Test-ISO 13997): X



Suitable for Contact with Foodstuff

PACKAGING INFORMATION	7 / S	8 / M	9 / L	10 / XL	11 / 2XL
MASTER CARTON DIMENSION	65X50X20 CM	65X50X20 CM	65X50X20 CM	65X50X20 CM	65X50X20 CM
NET WEIGHT	12.90 KG	13.40 KG	14.00 KG	14.50 KG	15.00 KG
GROSS WEIGHT	13.80 KG	14.40 KG	15.00 KG	15.60 KG	16.20 KG
CBM	0.065	0.065	0.065	0.065	0.065
HS CODE	40151910	40151910	40151910	40151910	40151910



LIMITATION OF USE

Properly fitting safety gloves are crucial for safety. Poorly-fitting gloves cause irritation and hinder hand movements. Ensure they meet your required safety level and fit comfortably for optimal protection and functionality. The glove should not be worn in areas where there's a risk of entanglement or where there are moving parts. Avoid using gloves if there are signs of damage or defects.